

# DUNLOP GROUT SEALER

Chemwatch Material Safety Data Sheet  
Issue Date: 28-Feb-2006  
NA477ECP

CHEMWATCH 4661-41  
Version No:3  
CD 2008/2 Page 1 of 7

---

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

---

### PRODUCT NAME

DUNLOP GROUT SEALER

### STATEMENT OF HAZARDOUS NATURE

Not considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation.

### OTHER NAMES

"grout sealer"

### PRODUCT USE

As cement based grout sealer.

### SUPPLIER

Company: Ardex NZ Pty Ltd  
Address:  
32 Lane Street  
Woolston  
Christchurch,  
NZL  
Telephone: +64 3384 3029  
Fax: +64 3384 9779

### HAZARD RATINGS



---

## Section 2 - HAZARDS IDENTIFICATION

---

### EMERGENCY OVERVIEW

#### HAZARD

Not hazardous  
No hazards determined by Chemwatch using GHS/HSNO criteria

### PRECAUTIONARY STATEMENTS

---

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

---

NAME	CAS RN	%
acrylic urethane resin	16889-77-3	10-60
bacteriacide		0-1
water	7732-18-5	30-60

continued...

# DUNLOP GROUT SEALER

Chemwatch Material Safety Data Sheet

Issue Date: 28-Feb-2006

NA477ECP

CHEMWATCH 4661-41

Version No:3

CD 2008/2 Page 2 of 7

---

## Section 4 - FIRST AID MEASURES

---

NEW ZEALAND POISONS INFORMATION CENTRE 0800 POISON (0800 764 766)  
NZ EMERGENCY SERVICES: 111

### SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

### EYE

If this product comes in contact with eyes:

- Wash out immediately with water.
- If irritation continues, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### SKIN

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

### INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

### NOTES TO PHYSICIAN

Treat symptomatically.

---

## Section 5 - FIRE FIGHTING MEASURES

---

### EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

### FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered to be a significant fire risk.
- Expansion or decomposition on heating may lead to violent rupture of containers.
- Decomposes on heating and may produce toxic/ irritating fumes.
- May emit acrid smoke.

### FIRE INCOMPATIBILITY

None known.

continued...

# DUNLOP GROUT SEALER

Chemwatch Material Safety Data Sheet  
Issue Date: 28-Feb-2006  
NA477ECP

CHEMWATCH 4661-41  
Version No:3  
CD 2008/2 Page 3 of 7

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

### EMERGENCY PROCEDURES

#### MINOR SPILLS

- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Wear impervious gloves and safety goggles.
- Trowel up/scrape up.
- Place spilled material in clean, dry, sealed container.
- Flush spill area with water.

#### MAJOR SPILLS

Minor hazard.

- Clear area of personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment as required.
- Prevent spillage from entering drains or water ways.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal.
- Wash area and prevent runoff into drains or waterways.
- If contamination of drains or waterways occurs, advise emergency services.

**Personal Protective Equipment advice is contained in Section 8 of the MSDS.**

---

## Section 7 - HANDLING AND STORAGE

---

### PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

### SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

### STORAGE INCOMPATIBILITY

Avoid contamination of water, foodstuffs, feed or seed.  
None known.

### STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.

continued...

# DUNLOP GROUT SEALER

Chemwatch Material Safety Data Sheet

Issue Date: 28-Feb-2006

NA477ECP

CHEMWATCH 4661-41

Version No:3

CD 2008/2 Page 4 of 7

Section 7 - HANDLING AND STORAGE

- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

---

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### EXPOSURE CONTROLS

The following materials had no OELs on our records

- acrylic urethane resin:
- water:

CAS:16889- 77- 3

CAS:7732- 18- 5

### MATERIAL DATA

Not available. Refer to individual constituents.

### INGREDIENT DATA

ACRYLIC URETHANE RESIN:

WATER:

No exposure limits set by NOHSC or ACGIH.

### PERSONAL PROTECTION

#### EYE

- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

#### HANDS/FEET

Wear general protective gloves, eg. light weight rubber gloves.

#### OTHER

No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Barrier cream.
- Eyewash unit.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

continued...

# DUNLOP GROUT SEALER

Chemwatch Material Safety Data Sheet  
Issue Date: 28-Feb-2006  
NA477ECP

CHEMWATCH 4661-41  
Version No:3  
CD 2008/2 Page 5 of 7

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas.

---

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

---

### APPEARANCE

Paste; mixes with water.

### PHYSICAL PROPERTIES

Mixes with water.

Molecular Weight: Not Applicable  
Melting Range (°C): Not Available  
Solubility in water (g/L): Miscible  
pH (1% solution): Not Available  
Volatile Component (%vol): Not Available  
Relative Vapour Density (air=1): Not Available  
Lower Explosive Limit (%): Not Available  
Autoignition Temp (°C): Not Available  
State: Non Slump Paste

Boiling Range (°C): Not Available  
Specific Gravity (water= 1): Not Available  
pH (as supplied): Not Available  
Vapour Pressure (kPa): Not Available  
Evaporation Rate: Not Available  
Flash Point (°C): Not Available

Upper Explosive Limit (%): Not Available  
Decomposition Temp (°C): Not Available  
Viscosity: Not Available

---

## Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

---

### CONDITIONS CONTRIBUTING TO INSTABILITY

Product is considered stable and hazardous polymerisation will not occur.

---

## Section 11 - TOXICOLOGICAL INFORMATION

---

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

##### EYE

Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

continued...

# DUNLOP GROUT SEALER

Chemwatch Material Safety Data Sheet

Issue Date: 28-Feb-2006

NA477ECP

CHEMWATCH 4661-41

Version No:3

CD 2008/2 Page 6 of 7

## Section 11 - TOXICOLOGICAL INFORMATION

---

### SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

### INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

### CHRONIC HEALTH EFFECTS

Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

## TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

### ACRYLIC URETHANE RESIN:

No data of toxicological significance identified in literature search.

### WATER:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

No significant acute toxicological data identified in literature search.

---

## Section 12 - ECOLOGICAL INFORMATION

---

No data for Dunlop Grout Sealer.

---

## Section 13 - DISPOSAL CONSIDERATIONS

---

- Recycle wherever possible or consult manufacturer for recycling options.
  - Consult State Land Waste Management Authority for disposal.
  - Bury residue in an authorised landfill.
  - Recycle containers if possible, or dispose of in an authorised landfill.
- 

## Section 14 - TRANSPORTATION INFORMATION

---

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA, IMDG

---

## Section 15 - REGULATORY INFORMATION

---

### REGULATIONS

Dunlop Grout Sealer (CAS: None):

No regulations applicable

continued...

# DUNLOP GROUT SEALER

## Chemwatch Material Safety Data Sheet

Issue Date: 28-Feb-2006

NA477ECP

CHEMWATCH 4661-41

Version No:3

CD 2008/2 Page 7 of 7

## Section 15 - REGULATORY INFORMATION

---

water (CAS: 7732-18-5) is found on the following regulatory lists;  
GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships  
IMO IBC Code Chapter 18: List of products to which the Code does not apply  
New Zealand Inventory of Chemicals (NZIoC)  
OECD Representative List of High Production Volume (HPV) Chemicals

No data available for acrylic urethane resin as CAS: 16889-77-3.

Specific advice on controls required for materials used in New Zealand can be found at  
<http://www.ermanz.govt.nz/search/registers.html>

---

## Section 16 - OTHER INFORMATION

---

NEW ZEALAND POISONS INFORMATION CENTRE

0800 POISON (0800 764 766)

NZ EMERGENCY SERVICES: 111

## EXPOSURE STANDARD FOR MIXTURES

"Worst Case" computer-aided prediction of spray/ mist or fume/ dust components and concentration:

Composite Exposure Standard for Mixture (TWA) :100 mg/m<sup>3</sup>.

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:  
[www.chemwatch.net/references](http://www.chemwatch.net/references).

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 28-Feb-2006

Print Date: 10-Jun-2008