

# DUNLOP GROUT SEALER

Chemwatch Material Safety Data Sheet  
Issue Date: 28-Feb-2006

CHEMWATCH 4661-41  
CD 2006/1 Page 1 of 8

---

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

---

### PRODUCT NAME

DUNLOP GROUT SEALER

### SYNONYMS

"grout sealer"

### PRODUCT USE

As cement based grout sealer.

### SUPPLIER

Company: Ardex Australia Pty Ltd

Address:

20 Powers Road

Seven Hills

NSW, 2147


AUS

Telephone: 1800 224 070

Fax: +61 2 9838 7817

### HAZARD RATINGS

Flammability  
Toxicity  
Body Contact  
Reactivity  
Chronic



SCALE:    Min/Nil=0            Low=1            Moderate=2            High=3            Extreme=4

---

## Section 2 - HAZARDS IDENTIFICATION

---

### STATEMENT OF HAZARDOUS NATURE

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

### POISONS SCHEDULE

None

### RISK

None under normal operating conditions.

### SAFETY

continued...

# DUNLOP GROUT SEALER

Chemwatch Material Safety Data Sheet

Issue Date: 28-Feb-2006

CHEMWATCH 4661-41  
CD 2006/1 Page 2 of 8

---

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

---

NAME	CAS RN	%
acrylic urethane resin	16889-77-3	10-60
bacteriacide		0-1
water	7732-18-5	30-60

---

## Section 4 - FIRST AID MEASURES

---

### SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

### EYE

If this product comes in contact with eyes:

- Wash out immediately with water.
- If irritation continues, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### SKIN

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

### INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

### NOTES TO PHYSICIAN

Treat symptomatically.

---

## Section 5 - FIRE FIGHTING MEASURES

---

### EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used. Use extinguishing media suitable for surrounding area.

### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

continued...

# DUNLOP GROUT SEALER

Chemwatch Material Safety Data Sheet

Issue Date: 28-Feb-2006

CHEMWATCH 4661-41

CD 2006/1 Page 3 of 8

Section 5 - FIRE FIGHTING MEASURES

---

## FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered to be a significant fire risk.
- Expansion or decomposition on heating may lead to violent rupture of containers.
- Decomposes on heating and may produce toxic/ irritating fumes.
- May emit acrid smoke.

## FIRE INCOMPATIBILITY

None known.

## HAZCHEM

None

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

## EMERGENCY PROCEDURES

### MINOR SPILLS

- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Wear impervious gloves and safety goggles.
- Trowel up/scrape up.
- Place spilled material in clean, dry, sealed container.
- Flush spill area with water.

### MAJOR SPILLS

Minor hazard.

- Clear area of personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment as required.
- Prevent spillage from entering drains or water ways.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal.
- Wash area and prevent runoff into drains or waterways.
- If contamination of drains or waterways occurs, advise emergency services.

## EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

water 500 mg/m<sup>3</sup>

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

water 500 mg/m<sup>3</sup>

other than mild, transient adverse effects without perceiving a clearly defined odour is:

water 500 mg/m<sup>3</sup>

continued...

# DUNLOP GROUT SEALER

Chemwatch Material Safety Data Sheet

Issue Date: 28-Feb-2006

CHEMWATCH 4661-41

CD 2006/1 Page 4 of 8

Section 6 - ACCIDENTAL RELEASE MEASURES

---

The threshold concentration below which most people will experience no appreciable risk of health effects:  
water 500 mg/m<sup>3</sup>

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		
else	>= 10%		

where percentage is percentage of ingredient found in the mixture

**Personal Protective Equipment advice is contained in Section 8 of the MSDS.**

---

## Section 7 - HANDLING AND STORAGE

---

### PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

### SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer
- Check all containers are clearly labelled and free from leaks.

### STORAGE INCOMPATIBILITY

Avoid contamination of water, foodstuffs, feed or seed.  
None known.

### STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

continued...

# DUNLOP GROUT SEALER

Chemwatch Material Safety Data Sheet

Issue Date: 28-Feb-2006

CHEMWATCH 4661-41  
CD 2006/1 Page 5 of 8

---

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### EXPOSURE CONTROLS

No data available: acrylic urethane resin as (CAS: 16889-77-3)

No data available: water as (CAS: 7732-18-5)

No data for Dunlop Grout Sealer.

### EXPOSURE STANDARDS FOR MIXTURE

"Worst Case" computer-aided prediction of spray/ mist or fume/ dust components and concentration:

"Worst Case" computer-aided prediction of spray/ mist or fume/ dust components and concentration:

Composite Exposure Standard for Mixture (TWA) :100 mg/m<sup>3</sup>.

### INGREDIENT DATA

ACRYLIC URETHANE RESIN:

No exposure limits set by NOHSC or ACGIH.

WATER:

No exposure limits set by NOHSC or ACGIH.

### PERSONAL PROTECTION

#### EYE

- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

#### HANDS/FEET

Wear general protective gloves, eg. light weight rubber gloves.

#### OTHER

No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Barrier cream.
- Eyewash unit.

The local concentration of material, quantity and

continued...

# DUNLOP GROUT SEALER

Chemwatch Material Safety Data Sheet

Issue Date: 28-Feb-2006

CHEMWATCH 4661-41

CD 2006/1 Page 6 of 8

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

conditions of use determine the type of personal protective equipment required.

For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

### ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas.

---

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

---

### APPEARANCE

Paste; mixes with water.

### PHYSICAL PROPERTIES

Mixes with water.

Molecular Weight: Not Applicable

Melting Range (C): Not Available

Solubility in water (g/L): Miscible

pH (1% solution): Not Available

Volatile Component (%vol): Not Available

Relative Vapour Density (air=1): Not Available

Lower Explosive Limit (%): Not Available

Autoignition Temp (C): Not Available

State: Non Slump Paste

Boiling Range (C): Not Available

Specific Gravity (water=1): Not Available

pH (as supplied): Not Available

Vapour Pressure (kPa): Not Available

Evaporation Rate: Not Available

Flash Point (C): Not Available

Upper Explosive Limit (%): Not Available

Decomposition Temp (°C): Not Available

Viscosity: Not Available

---

## Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

---

### CONDITIONS CONTRIBUTING TO INSTABILITY

Product is considered stable and hazardous polymerisation will not occur.

---

## Section 11 - TOXICOLOGICAL INFORMATION

---

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may

continued...

# DUNLOP GROUT SEALER

Chemwatch Material Safety Data Sheet

Issue Date: 28-Feb-2006

CHEMWATCH 4661-41

CD 2006/1 Page 7 of 8

## Section 11 - TOXICOLOGICAL INFORMATION

---

produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

### EYE

Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

### SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

### INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

### CHRONIC HEALTH EFFECTS

Long-term exposure to the product is not thought to produce chronic effects adverse to health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

### TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances

#### ACRYLIC URETHANE RESIN:

No data of toxicological significance identified in literature search.

#### WATER:

No significant acute toxicological data identified in literature search.

---

## Section 12 - ECOLOGICAL INFORMATION

---

No data for Dunlop Grout Sealer.

---

## Section 13 - DISPOSAL CONSIDERATIONS

---

- Recycle wherever possible or consult manufacturer for recycling options.
  - Consult State Land Waste Management Authority for disposal.
  - Bury residue in an authorised landfill.
  - Recycle containers if possible, or dispose of in an authorised landfill.
- 

## Section 14 - TRANSPORTATION INFORMATION

---

### HAZCHEM

None

continued...

# DUNLOP GROUT SEALER

Chemwatch Material Safety Data Sheet

Issue Date: 28-Feb-2006

CHEMWATCH 4661-41

CD 2006/1 Page 8 of 8

Section 14 - TRANSPORTATION INFORMATION

---

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN,IATA,IMDG

---

## Section 15 - REGULATORY INFORMATION

---

### POISONS SCHEDULE

None

### REGULATIONS

No regulations applicable

water (CAS: 7732-18-5) is found on the following regulatory lists;

Australia Inventory of Chemical Substances (AICS)

OECD Representative List of High Production Volume (HPV) Chemicals

No data available for acrylic urethane resin as CAS: 16889-77-3.

---

## Section 16 - OTHER INFORMATION

---

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 28-Feb-2006

Print Date: 28-Feb-2006