

Ready-to-Go RENDER



A Ready-to Go Render which has been premixed to an optimal consistency. Suitable for indoor and outdoor projects over a wide variety of surfaces including brickwork, AAC blocks, FC sheet and concrete, the easy trowel, easy float formulation of Dunlop renders makes it perfect for the DIYers and Trade alike.

APPLICATION RANGE

Suitable for rendering walls, both indoor and outdoor, at an application thickness from 2-5 mm.

It can be applied over the following surfaces:

- Brickwork
- Blue board
- Concrete blockwork
- Concrete walls
- AAC (autoclaved aerated concrete) panels and blocks

If a higher build is required on an uneven surface, use DUNLOP MULTIPURPOSE ACRYLIC RENDER as a base coat and use DUNLOP Ready-to-Go RENDER as a finishing coat.

SURFACE PREPARATION

Clean off dust, oil, grease and all loose contaminating materials or coatings. Green concrete should be allowed to cure for 28 days prior to rendering.

If dry and porous, dampen the surface to be rendered by brushing or sponging the surface or applying a light mist spray of water to prevent rapid drying of the render.

Jointing of all FC sheet and blueboard should be carried out as per manufacturers instructions.

MIXING

No mixing required.

APPLICATION

Trowel-On Procedure

- 1 Apply the render with a steel trowel, evenly spreading the mix over the surface.
- 2 After 10-30 minutes, depending on ambient and surface conditions, work can begin on the surface finish. The surface finish can be dense and smooth by using a wooden or plastic float or coarse and sandy by using a sponge to give the required effect.

Roll-On Procedure

- 1 Apply the render to the surface with a textured roller, rolling gently in a downward motion, repeating the motion 3 times.
- 2 Roll horizontally over applied render removing excess render.
- 3 Use a plastic trowel in an upward motion to ensure the render is evenly spread and repeat steps 1-3.
- 4 If a second coat is required, wait 6-8 hours for the first coat to dry.

FINISHING

After 10-30 minutes, depending on ambient and surface conditions, work can begin on the surface finish. The surface finish can be dense and smooth by using a wooden or plastic float or coarse and sandy by using a sponge to give the required effect. The roll-on mix and a textured roller can be used to achieve a textured surface finish.

DRYING TIME

The render surface is touch dry in 2-4 hours @ 23°C. A second coat may be applied after 24 hours and the surface will reach full cure after 7 days. Before application of a decorative finish (i.e. paint) allow the render to cure for a minimum of 1 day for each 2mm thickness of the render. It is recommended that Ready-to-Go RENDER is overcoated with a quality acrylic paint to protect the finished surface from dust and wind borne contaminants that can adversely effect the appearance and longevity of the surface. Cold, damp or humid conditions may lengthen the drying time.

COVERAGE

Coverage will vary depending on the condition of the surface and site conditions. As a guide, 10L of DUNLOP Ready-to-Go RENDER will cover approximately 6m² at 1mm thickness or 2m² at 3mm thickness.

CLEAN UP

Clean all tools in water immediately after use.

SHELF LIFE

12 months when stored in a dry place, in original unopened packaging.

PRECAUTIONS

DUNLOP Ready-to-Go RENDER is not suitable for use over floors and is not suitable for application over painted surfaces. Do not apply in temperatures below 5°C or above 35°C or application in extreme conditions such as high wind or direct sunlight. Protect the render from rain after application for 48 hours.

SAFETY DATA

The presence of cement in the product gives an alkaline mortar which may cause some irritation if prolonged contact with skin takes place. Keep out of the reach of children. Use gloves to prevent skin irritation. Avoid inhaling dust by using a dust mask. Wash immediately with plenty of water if material enters the eyes. Additional information is in the Material Safety Data Sheet (MSDS) available at www.dunlopdij.com



Ready-to-Go RENDER

DUNLOP GUARANTEE

Product is guaranteed for 10 years when installed to manufacturers instructions. Manufactured under a quality system certified as complying with ISO 9001 by an accredited certification body.

USER NOTES

The technical details and recommendations contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is the responsibility of the user to ensure that the products are used in accordance with DUNLOP product instructions and in applications for which they are intended.

TECHNICAL INFORMATION

Product Characteristics

Colour White

Characteristics of Mix

Ready-mixed

Application Properties

Touch Dry 2-4 hours

Recoat Time 24 hours

Full Cure 7 days

TOLL FREE

1800 222 841 (AU)

0800 224 070 (NZ)

www.dunlopdij.com

ARDEX Australia Pty Ltd ABN 82 000 550 005
7/20 Powers Rd, Seven Hills NSW 2147

ARDEX Australia Pty Ltd
NSW Ph (02) 9851 9199 Fax (02) 9838 7970
VIC Ph (03) 8339 3100 Fax (03) 9308 9332
QLD Ph (07) 3817 6000 Fax (07) 3881 3188
SA Ph (08) 8406 2500 Fax (08) 8345 3207
WA Ph (08) 9256 8600 Fax (08) 9455 1227

ARDEX New Zealand Ltd
Ph (03) 373 6900 Fax (03) 3849 779