

Ready-to-Go COLOURED GROUT



DUNLOP® Ready-to-Go COLOURED GROUT is a ready-mixed, easy to apply grout that is suitable for walls and floors in indoor and outdoor* situations. DUNLOP® Ready-to-Go COLOURED GROUT can be used in tile joints between 1mm and 5mm wide. The non-cracking formulation also contains Microban antifungal protection that will prevent mould and mildew growth for the lifetime of the grout.

*** When grouting outdoors, the project will need to be protected from the weather for 7 days until the grout reaches full cure.**

JOINT PREPARATION

Ensure joints are clean and free from excess adhesive. The depth of the grout joint should be at least half its width. Remove all tile spacers and do not grout until the tiling has set firmly.

APPLICATION

1. Prior to grouting, it is advisable to check ease of cleaning with the tiles being used.
2. Cut the tapered nozzle so that the opening of the nozzle is as wide as necessary for your project. Reseal the nozzle and holding the bottle upside down, shake for 15 seconds.
3. Squeeze grout out of bottle and apply the grout into the joints whilst holding the bottle at a 90° angle to the surface being grouted.
4. Ensure the grout has been compacted firmly into the joint using a grout float or squeegee.
5. Minimise any excess grout from the surface of the tile by scraping with a grout float or squeegee. Allow the grout to firm up in the joint for approximately 15 minutes.
6. Remove excess grout from the surface of the tiles with a dense, damp, small-pored sponge working diagonally across the joint. Rinse the sponge frequently in clean water. Use a minimum amount of water when cleaning the tile surface and smoothing the joints so as to minimise water float shade variation and shrinkage.
6. When DUNLOP® Ready-to-Go COLOURED GROUT has sufficiently hardened in the tile joints, polish the tile surface with a clean dry cloth.
7. When grouting outdoors, it is essential to protect the grouted area from all extremes of climate until the grout has reached full cure which is 7 days.

COVERAGE

The table below shows approximate coverage (square metres) per 800g bottle. Allow an extra 10-15% for wastage due to application technique, tile types and job site variations.

Tile Size (LxWxD)	1.5mm	3mm	5mm
25x25x4	1.04	0.52	0.31
100x100x8	2.08	1.04	0.63
200x200x8	4.17	2.08	1.25
330x330x9	6.11	3.05	1.83

DRYING TIME

Initial set is after 24 hours at 23°C and 50% relative humidity after which the shower walls can be exposed to water. Shower floors can be used after 3 days. Full cure after 7 days. Allow longer for lower temperatures, dense tiles or high relative humidity.

CLEAN UP

All tools should be cleaned with warm water immediately after use.

SHELF LIFE

12 months when stored in the original unopened packaging, in a dry place at 23°C and 50% relative humidity.

CAUTION

Do not use in expansion or movement joints, use DUNLOP COLOURED SILICONE. Not suitable for use in immersed situations such as swimming pools. Instead, use DUNLOP® Flexible COLOURED GROUT White 200 mixed with diluted DUNLOP® PRIMER AND ADDITIVE. Depending on application technique, some concavity may occur in wider joints.

SAFETY

Wear gloves when working. If the product enters the eyes, wash with clean water for at least 15 minutes and seek medical advice. If swallowed do not induce vomiting, give a glass of water and contact a doctor.

TECHNICAL DATA

Product Identity:

Form: Soft Paste
Colour: White, Jet Black, Buff, Slate Grey
Size: 800g

Application Properties

Mixing Ratio: No Mixing Required
Working Time: 15-30 minutes (@ 25°C, 50% RH)

DUNLOP GUARANTEE

Product is guaranteed for 10 years when installed to manufacturers instructions. The guarantee does not cover shade variations and efflorescence as these are caused by factors beyond the manufacturers control, including project conditions, finishing techniques and uneven drying conditions.



Ready-to-Go COLOURED GROUT

USER NOTES

The technical details and recommendations contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is the responsibility of the user to ensure that the products are used in accordance with DUNLOP product instructions and in applications for which they are intended.

ARDEX AUSTRALIA PTY LTD. ABN 82 000 550 005
20 Powers Road, Seven Hills NSW 2147 Australia

Microban and the Microban symbol are the trademarks of the Microban products Company, Huntersville NC.

ARDEX Australia Pty Ltd

NSW	Ph (02)9851 9100	Fax (02)9838 7970
VIC	Ph (03)9308 9255	Fax (03)9308 9332
QLD	Ph (07)3817 6000	Fax (03)3881 3188
SA	Ph (08)8268 2511	Fax (08)8345 3207
WA	Ph (08)9455 1644	Fax (08)9455 1227

ARDEX New Zealand Ltd

Auckland	Ph (09)5800 005	Fax (09)5799 963
Wellington	Ph (04)5685 949	Fax (04)5686 376
Christchurch	Ph (03)3843 029	Fax (03)3849 779

RTG_0709

TOLL FREE SERVICE:
1800 222 841(Aust) 0800 224 070 (NZ)

www.dunlopdij.com